

PACKAGED PUMPING STATION

Tricel Twin 800-1500-10

Part Code 107006



A fully automatic twin pump packaged pumping station suitable for pumping grey and foul water to a higher level when gravity drainage is not possible or economical to install.

The system provides up to 450 litre storage capacity depending inlet depth. It is ideal for accepting waste from an extension, outbuilding, basement or similar.

Two stainless steel Xylem Domo pumps provide reliable and effective pumping of grey and foul water.

It can accept foul waste if the property also has another method of removing foul waste. Contact our Sales Team if you require a foul water packaged pumping station to serve the whole property.

The system comprises our award-winning polyethylene chamber, internal Class E PVC pipework and fittings, brass valves, two pedestal-mounted automatic pumps, stainless steel guide rails and lifting chains, and an external compression adaptor for discharge to 63 mm OD MDPE. A pedestrian duty 600 mm x 450 mm solid top access cover is included.

It is simple to install as inlets can be positioned to your site's requirements. Inlet information to be supplied at time of order, or they can be drilled on site.

The system is built to last and designed to be easy to service.

SYSTEM OVERVIEW



Two pedestal-mounted automatic Xylem Domo stainless steel pumps with guide rails and lifting chains



2″ brass valves 3 mm MDPE discharge 4 110 mm inlet 50 mm cable duct 50 mm vent duct

2" Class E PVC pipework

Access cover, solid top, locking, galvanised steel, PP frame, FACTA A

KEY FEATURES

- Vortex impellor for high flow rates
- Twin pumps for backup if one of the pumps fail
- Up to 450 litres storage capacity
- 60° benching
- Compact chamber for limited space installations
- Ideal for accepting waste from an extension, outbuilding, basement or similar application
- 600 mm x 450 mm pedestrian duty access cover
- Variable inlet positions to suit site
- · A range of alarms and remote alerts are available
- · Quick and simple to install

SPECIFICATIONS

This system complies with:

- BS EN 12050-2:2015 Wastewater lifting plants for buildings and sites. Lifting plants for faecal-free wastewater.
- BS EN 12050-3:2015 Wastewater lifting plants for buildings and sites. Lifting plants for limited applications.

ACCESSORIES





HIGH LEVEL ALARM (RECOMMENDED)



AquaSafe Alarm

High level alarm alert HLA recorded alert Service due alert Volt-free contacts for BMS Alarm battery backup

106993


Tricel Killarney, Ballyspillane Industrial Estate, Killarney, Co Kerry, Ireland Tel: +353 (0)64 663 2421 | Email: sales@tricel.ie | www.tricel.ie



PACKAGED PUMPING STATION

Tricel Twin 800-1500-10

Part Code 107006



G

н

T.

J


κ

L

- 50 mm cable duct Α
- В 63 mm OD MDPE discharge
- 2" brass gate valve С
- D 2" brass swing check valve
- Ε Tank-grade polyethylene chamber
- F Access cover 600 mm x 450 mm


CHAMBER DIMENSIONS


Permitted connection positions



Discharge

only






Capacities indicative from lowest inlet invert. rilling

allowed	vents only	allowed

PUMP SPECIFICATIONS (PER PUMP)

Pump	Domo 10VX	
Number of pumps	Two	
Impellor type	Vortex	
Control	Automatic	
Power supply	230 VAC	
Rated current	5.9 A	
Motor rating (P2)	750 W	
Discharge size	2″	
Free passage	50 mm	
Max. vertical output	7.7 m	
Max. flow rate	6.7 l/s	
Max liquid temp.	<35 °C	
Cable length	10 m	
Weight	13.6 kg	



CHAMBER SPECIFICATIONS

Internal pipework	2" OD Class E PVC
Discharge pipework	63 mm OD MDPE
Lifting eyes	4 no
Max. storage capacity	450 litres
Chamber material	Tank-grade polyethylene
Dimensions (Ø x H)	900 x 1500 mm
Clear opening	600 x 450 mm

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice. Tricel (Killarney) Unlimited Company trading as Tricel.

850

50 mm vent duct

100 mm ID inlet

Concrete backfill

Guide rail and lifting chain

Reinforced concrete sump

Choice of automatic pumps